

In the Specification

Please replace the following amended paragraph:

**The paragraph on Page 21 lines 3 to 18, insert the following paragraph.**

The air handling system of the bench includes the plenum 58 50, the fan 60 and the duct 52. The plenum 50 comprises a rectangular housing standing on the concrete floor 11 and defining a top surface 69 on which the bench tray 55 sits. The bench tray is mounted for pivotal movement about a hinge 70 at one corner of the housing forming the plenum as best shown in Figure 3. The bench tray includes a support member 71 which is pivotally connected at the hinge 70 and can fold downwardly to a closed position sitting on the top surface 69. In the position shown in Figure 3, the support member 71 is pivoted in a clockwise direction by manual lifting of the bench tray 55 while controlled and assisted by an air cylinder 72. Others of the benches may pivot in the same or opposite directions as required. The slide bearings 68 are connected between the tray 55 itself and a support member 71 so that the tray slides back and forth on the bearings relative to the support member, when the support member is in the lowered position. An interlock (not shown) is provided to prevent sliding movement when the support member is unlocked for lifting so as to prevent uncontrolled sliding movement when the tray is moved to the open position shown in Figure 3.

**The paragraph on Page 31 lines 8 to 14, Insert the following paragraph.**

One of the lighting fixtures 112 on the rail 113 is shown in more detail in Figures 11 to 14. This comprises a mounting bracket 150, a reflector housing 151 and a bulb support 152. The mounting bracket 150 comprises a base plate 154 and two side plates 155 and 156 arranged at right angles to the base plate. Each mounting plate 155, 156 is generally U shaped with two depending legs each at a respective side of the base plate 150. Each depending leg has a mounting slot 157 which is arcuate around a pivot axis extending approximately centrally along the plane of the base plate 150.